


# I-Force® and I-Force Slim

ANSI • CE • CSA • AS • Ballistic •



Dual pane lens // Outer polycarbonate lens protects against the environment, while inner acetate lens prevents fogging // Outside lens is coated with anti-fog treatment // Quick release interchangeable temples and strap // Removable vented flame resistant foam carriage // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards

## I-Force Black Frame | 4 Variations

- SB7010SDT ••••• Clear Dual Pane H2X AF
- SB7020SDT ••••• Gray Dual Pane H2X AF
- SB7030SDT ••••• Amber Dual Pane H2X AF
- SB7080SDT ••••• I/O Mirror Dual Pane AF

## I-Force Slim Black Frame | 3 Variations

- SB7010SDNT ••••• Clear Dual Pane H2X AF
- SB7020SDNT ••••• Gray Dual Pane H2X AF
- SB7080SDNT ••••• I/O Mirror Dual Pane AF



148 mm



157 mm



### WATCH THE VIDEO

Vimeo.com/Pyramex/I-Force



**i** I-Force Slim is about 6% smaller than the I-Force.

### I-Force General Specifications

Weight: 48 gm  
 PD: 68 mm  
 Bridge: 14.5 mm  
 Lens base: 8 curve  
 Lens size diagonal: 72 mm  
 Lens size vertical: 51 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 165 mm  
 Overall width (hinge - hinge): 165 mm  
 Closest point between lens: 16 mm

### Materials

Lens: polycarbonate + acetate  
 Foam: chloroprene rubber foam  
 Nosepiece: chloroprene rubber foam  
 Front carriage: nylon  
 Foam frame: nylon  
 Goggle + Temple strap: polyester  
 Hinge: polycarbonate  
 Ratchet: polycarbonate  
 Temples: polycarbonate  
 Temple tips: nylon  
 Temple strap holder: nylon

### I-Force Slim General Specifications

Weight: 47.5 gm  
 PD: 64 mm  
 Bridge: 14.5 mm  
 Lens base: 8 curve  
 Lens size diagonal: 67 mm  
 Lens size vertical: 51 mm  
 Lens thickness: 1.8 mm  
 Overall length (lens - tip): 160 mm  
 Overall width (hinge - hinge): 144 mm  
 Closest point between lens: 16 mm

Part No.	Lens Marking	Temple Marking
SB7010SDT	P Z87+U6 L1.3	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB7020SDT	P Z87+ U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB7030SDT	P Z87+S	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB7080SDT	P Z87+U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB7010SDNT	P Z87+U6 L1.3	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB7020SDNT	P Z87+ U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SB7080SDNT	P Z87+U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.3: 85% Max. Visible Light  
 L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact