



TECHNICAL DATA SHEET

ZT200



- Tight fitting eyewear for excellent protection
- Closed-cell foam brow guard to protect from falling debris
- Wide field-of-view to help avoid side hazards
- Soft touch contact points for comfortable long-term wear
- Adjustable nose pads for comfortable and optimal optical fit
- Lanyard included for added secure fit for rugged jobs

Frame Specifications

Frame size: 54 20 126

• Eyesize: 54

B: 34.1ED: 56.2

• Lenses:

o **Phoenix or Trivex**

o **Polycarbonate**

o **Polarized**

Plastic (not impact rated)

o Glass not recommended

Coatings: All coatings available

• Colors: Black, Gray, Navy, Purple, Camo

• Temple: Straight

Sideshields: Integrated

Breakaway lanyard: Included

Frame Materials

Frame: NylonBridge: Nylon

Lens Carrier: NylonTemple: Polycarbonate

Temple: FolycarbonTemple tips: TPR

Nose pads: TPR

Seal: Polyester PUR

• Temple Screws: Stainless Steel

Standards & Rx

- Tested to and meets the requirements of ANSI Z87.1-2010
- Non-Conductive by testing to ASTM 149 modified for safety eyewear passing 1,000 volts
- Glass not recommended
- No Rx limitations within normal ranges
- Phoenix, Trivex and polycarbonate recommend as impact rated



2925 Gary Drive, Plymouth, IN 46563 USA Customer Service: 800.982.2828 http://www.hoyavision.us/safetyRx/



Lit. Code: 34085