



TECHNICAL DATA SHEET

ZT35



- **Tight fitting eyewear for excellent protection against dirt, debris and splash**
- **Soft, flexible seal to conform to all faces**
- **Wide field-of-view to help avoid hazards**
- **Headstrap provided for demanding work**
- **Removable seal for use when dust and splash protection is not required**
- **Removable temples, seal and headstrap allow eyewear to be adaptable to any job**

Frame Specifications

- **Frame size: 57 20 125**
- **Eyesize: 57**
- **B: 37.3**
- **ED: 58.5**
- **Lenses:**
 - **Phoenix or Trivex**
 - **Polycarbonate**
 - **Polarized**
 - **Plastic (not impact rated)**
 - **Glass not recommended**
- **Coatings: All coatings available**
- **Colors: Matte Gray, Shiny Black, Camo**
- **Temple: Straight-removable**
- **Sideshields: Integrated**
- **Included: Headstrap, removable seal removable temples**

Frame Materials

- **Frame: Nylon**
- **Bridge: Nylon**
- **Lens Carrier: Nylon**
- **Temple: Nylon**
- **Temple tips: TPR**
- **Nose pads: TPR**
- **Seal: TPR**
- **Temple Screws: Stainless Steel**

Standards & Rx

- **Tested to and meets the requirements of ANSI Z87.1-2010**
- **Non-Conductive by testing to ASTM 149 modified for safety eyewear passing 1,000V**
- **No Rx limitations, within normal ranges**
- **Phoenix, Trivex and polycarbonate recommend as impact rated**