

TECHNICAL DATA SHEET

ZT400



- Tight fitting eyewear for excellent protection against dirt and debris.
- Wide field-of-view to help avoid hazards
- Indirect venting to create even air flow and prevent fogging
- Adjustable soft-feeling nose pad for allday comfort and adaptable fitting
- Adjustable, temple tips for snug fit; keeps eyewear in place
- Head strap included for demanding jobs

Frame Specifications

• Frame size: 57 15 133

Eyesize: 57B: 33.6ED: 58.0

Lenses:

o Phoenix or Trivex

o **Polycarbonate**

o **Polarized**

Plastic (not impact rated)

o Glass not recommended

Coatings: All coatings available

Colors: Black, Navy, Tan, Charcoal

• Temple: Straight

Sideshields: Integrated

Included: Headstrap

Frame Materials

Frame: NylonBridge: Nylon

Lens Carrier: Nylon

Temple: Nylon

• Temple tips: TPR

Nose pads: TPRTemple Pin: Nylon

 Tested to and meets the requirements of ANSI Z87.1-2010

Standards & Rx

- Non-Conductive by testing to ASTM 149 modified for safety eyewear passing 1,000V
- No exposed metal parts

Lit. Code: 34099

- No Rx limitations, within normal ranges
- Phoenix, Trivex and polycarbonate recommend as impact rated

HOYA Safety Division

2925 Gary Drive, Plymouth, IN 46563 USA Customer Service: 800.982.2828 http://www.hoyavision.us/safetyRx/

