

CONAIRE™

ANSI • CSA •



Lightweight //
Rubber temples

Black Frame | 3 Variations

- SB10710D •• Clear
- SB10720D •• Gray
- SB10734D •• UV400 Blue Block

i SB10734D offers high contrast, 100% UV protection with an anti-reflective coating.



MARKINGS

Part No.	Lens Marking	Temple Marking
SB10710D	P Z87 + U6	P Z87 + / P c SEI Z94.3
SB10720D	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
SB10734D	P Z87 + U6	P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 UV Filter Transmittance
 U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

SPECIFICATIONS

Measurements

Weight: 26.8 gm
 PD: 64 mm
 Bridge: 10.8 mm
 Lens base: 6 curve
 Lens size diagonal: 54.5 mm
 Lens size vertical: 39.5 mm
 Lens thickness: 2.3 mm
 Overall length (lens - tip): 153 mm
 Overall width (hinge - hinge): 129 mm
 Closest point between temple tips: 90.5 mm
 Closest point between lens: 17.5 mm

Materials

Lens: polycarbonate
 Side Shield: polycarbonate
 Frame: transparent nylon
 Temples: polycarbonate
 Temple tips: thermoplastic rubber
 Screw: stainless steel