



**XSG®** ANSI • CE • CSA •



Flame resistant foam padding  
// Strap has quick-fit retainer  
// Interchangeable temples  
and strap included






**Black Frame | 4 Variations**

	GB4010ST •••	Clear <b>H2X</b> AF
	GB4010STM •••	Clear <b>H2MAX</b> AF
	GB4020ST •••	Gray <b>H2X</b> AF
	GB4080ST •••	I/O Mirror AF

**XSG® Readers** ANSI • CSA •

Flame resistant foam padding // Strap has quick-fit retainer // Interchangeable temples and strap included

**Black Frame | 3 Variations**

	GB4010STR15 ••	Clear <b>H2X</b> AF	+1.5 Mag
	GB4010STR20 ••	Clear <b>H2X</b> AF	+2.0 Mag
	GB4010STR25 ••	Clear <b>H2X</b> AF	+2.5 Mag



## XSG®

### General Specifications

Weight: 28 gm  
 PD: 68 mm  
 Bridge: 13.7 mm  
 Lens base: 8 curve  
 Lens size diagonal: 66.3 mm  
 Lens size vertical: 44 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 163 mm  
 Overall width (hinge - hinge): 136.5 mm  
 Closest point between temple tips: 56 mm  
 Closest point between lens: 18.5 mm  
 Strap length: 420 mm

### Materials

Lens: polycarbonate  
 Foam: polycarbonate & ethylene vinyl acetate  
 Frame: nylon  
 Temples: polycarbonate & polyvinyl chloride  
 Strap: polyester  
 Screw: stainless steel  
 Nosepiece: ethylene vinyl acetate

Part No.	Lens Marking	Temple Marking
GB4010ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
GB4010STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
GB4020ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
GB4080ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 X: Tested Anti-fog

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light  
 L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices

## XSG® Readers

### General Specifications

Weight: 35 gm  
 PD: 68 mm  
 Bridge: 13.7 mm  
 Lens base: 8 curve  
 Lens size diagonal: 66.3 mm  
 Lens size vertical: 44 mm  
 Lens thickness: 2.3 mm  
 Overall length (lens - tip): 163 mm  
 Overall width (hinge - hinge): 136.5 mm  
 Closest point between temple tips: 56 mm  
 Closest point between lens: 18.5 mm  
 Strap length: 420 mm

### Materials

Lens: polycarbonate  
 Foam: polycarbonate & ethylene vinyl acetate  
 Frame: nylon  
 Temples: polycarbonate & polyvinyl chloride  
 Strap: polyester  
 Screw: stainless steel  
 Nosepiece: ethylene vinyl acetate

Part No.	Lens Markings	Temple Markings
GB4010STR15	P Z87 + U6	+1.50 P Z87 - 2+ / P c SEI Z94.3
GB4010STR20	P Z87 +	+2.00 P Z87 - 2+ / P c SEI Z94.3
GB4010STR25	P Z87 +	+2.50 P Z87 - 2+ / P c SEI Z94.3

### Lens Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 UV Filter Transmittance  
 U6: .01% max effective far UV • .1% max near UV

### Temple Marking Symbols

+1.50: magnification of +1.5  
 +2.00: magnification of +2.0  
 +2.50: magnification of +2.5  
 +3.00: magnification of +3.0  
 P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 - 2: Rx  
 +: High impact  
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices